

LARGE FORMAT PHOTO PRINTERS

SURECOLOR SC-P6530E/P6530D/ P8530D/P8530DL/P8530DM



AMPLIFY YOUR IDEAS WITH TOP CLASS PRINT QUALITY.



Transform your ideas into striking true-to-life prints with Epson's P-series printers.

Nothing beats seeing life injected into your ideas, turning them into picturesque prints in vivid and vibrant colours with top-class accuracy. Equipped with the Epson's proprietary PrecisionCore™ MicroTFP printheads, the Epson SureColor P-Series photographic printers take pride in their precise and reliable print productivity, along with the colour-accurate reproduction with Epson genuine UltraChrome PRO 6 inks. With high installation flexibility and seamless printing workflow, increase your print efficiency today!









Highest Standards in Print

The additional grey ink in the UltraChrome PRO 6 inks offers smooth and natural colour gradation in every print.

Installation Flexibility

Flat top design allows for easy placement of printer in challenging and narrow spaces, giving businesses more options in installation.

Boosted Efficiency

Improved print speeds and continuous automatic printing with dual rollers* help ensure high productivity with minimal downtime.

*Applicable for SC-P6530D/P8530D/P8530DL.

Consistently and efficiently delivering top-notch gallery-quality photos, Epson's SureColor P-Series employs an unprecedented level of innovative technology. Coupling PrecisionCore™ technology with UltraChrome PRO 6 Inks, high accuracy and resolution can be achieved allowing the finest details to stand out.



PRINTHEAD TECHNOLOGY

Epson's PrecisionCore MicroTFP printheads deliver precise ink drop control with variable-sized droplets, allowing every print to be reproduced in crisp clarity and sharpness. For photos that require extremely precise line details, definite sharp text and striking colours, trust your P-series printers to deliver world-class accuracy for every print.



INK TECHNOLOGY

Accurate Colour Reproduction

Be ready to impress with vivid prints by your Epson P-series printers. Delivering superb image quality with true-to-life colour accuracy, Epson's UltraChrome PRO 6 inks bring prints to a whole new level of professionalism.



Gallery Standards

6-Colour ink set delivers exceptionally wide colour gamut and high black density, producing photographic prints that are of gallery standards.







Professional Black-and-White prints Photographic prints

Wide Variety of Media

Professional printing can be done on a variety of media, such as artist canvas or premium photo papers.



Epson UltraChrome PRO 6 ink delivers professional

quality output with either high-capacity ink cartridges

or replaceable ink packs*, depending on your printing

High-Capacity Ink System

Gloss media

Prints That Last

Water and smudge resistant

Epson's UltraChrome PRO 6 inks are water-, smudgeand fade-resistant, allowing prints to be durable and long-lasting.









Ink cartridges

needs.

*Ink packs for SC-P8530DL only

Smoother Gradation for Professional Perfection

Utilising the innovative two-level black ink technology that simultaneously employs Photo Black and Matte Black, Epson's UltraChrome PRO 6 inks produce rich true-to-life black density and grey balance to ensure top-notch quality in every print. Generating smooth gradients, transitions, and neutral grayscale in every photo.







SERIES

ALL-NEW ERGONOMIC DESIGN

Compact with Installation Flexibility

With a flat back design, Epson's P-series printers can be easily arranged in a plethora of layouts according to your space's fit. With high installation flexibility, the compact printers maximise space usage and fit perfectly, even in narrow spaces.



Up to 44" Wide Dual Roll* Design

Management of prints have never been made easier with the dual roll 44" wide-format media* configuration that helps maximise productivity and increase efficiency.



Seamless Operation

Operating with top-tier reliability, the Epson SureColor P-series saves time and manpower with the Automatic Roll switching, simplifying the loading of new media rolls. *Only available for P6530D, P8530D/DL/DM. Minimising downtime, the seamless operation ensures continuous printing and smooth operation.







Automatic Roll-Media Feed

utomatic Roll Switc

Production Stac

USER-FRIENDLY FEATURES

Conveniently check the status of your professional prints with user-friendly features on your P-series printers.



Final printouts are held in a retractable print basket. The in-built storage space minimises clutter.



USB Direct Print without the need of a PC.

The 4.3-inch full-coloured touch panel allows easy and quick access to print jobs and printer function.



LED light allows operators to check on the print status conveniently and quickly.



EFFICIENT WORKFLOW MANAGEMENT

Epson Smart Panel

With the Epson Smart Panel app, users can set up, monitor, print and scan through an iOS or Android device.

Conveniently set up, monitor, print, and scan on your Epson printers and easily commence print jobs from your fingertips. With a wide variety of configuration features, you can also customise the app according to your requirements into an all-in-one management app.



Printing with Adobe PostScript

Adobe PostScript allows powerful image processing and reproduction that guarantees seamless and worry-free printing of vivid, crisp prints. With the all-new Adobe Embedded Print Engine, your business will no longer have to fret about colour accuracy and precise line printing with improved transparent and overprint layers. *Only available for P6530D, P8530D/DL/DM

Accurate









Epson Cloud Solution PORT

Managing your printers is made easy and hassle-free with Epson's Cloud Solution PORT. Operators can monitor equipment and printer fleet across different sites from production floor or remotely, on PC or a mobile device without fuss. Boost operational efficiency by controlling, analysing and managing your printer fleet centrally from one intuitive interface while troubleshooting any rare issues.





Epson Cloud Solution
PORT

SPECIFICATIONS

MODEL NUMBER	SC-P6530E	SC-P6530D		
SKU Number	C11CJ48402	C11CJ49402		
Printing Technology				
Printing Method	PrecisionCore Inkjet Technology, Variable	e-Sized Droplet Technology		
Print Head	PrecisionCore MicroTFP Printhead			
Nozzle Configuration	9,600 Nozzles			
Black	Pk:1,600, Mk:1,600			
Colour Maximum Resolution	C:1,600, M:1,600, Y:1,600, Gray:1,600			
Minimum Ink Droplet Volume	2,400 x 1,200 dpi 3.5pl			
Printing Specifications	3.3pi			
Print Speed	A1 Size Premium Glossy Photo Paper 1 EPSON Standard (sRGB) / Quality: 111			
Margin Roll Paper	Right: Min. 3mm ⁻¹ / Left : Min. 0mm ⁻¹			
Cut Sheet	Top: Min. 3mm ⁻¹ / Bottom: Min. 1mm ⁻¹			
Minimum Line Width	0.08 mm ⁻² (0.02 mm ⁻³)			
Ink System				
Ink Type	Pigment Ink			
Ink Brand Name	UltraChrome Pro 6 Ink			
Colour	Cyan, Magenta, Yellow, Grey, Photo Black, Matte Black			
Ink Capacity	350, 700 ml			
Ink Case	Ink Cartridge	Ink Cartridge		
Paper Handling	Rall (Single Rall)	Poll (Double Poll)		
Paper Path	Roll (Single Roll), Cut Sheet (Manual Feed),	Roll (Double Roll), Cut Sheet (Manual Feed),		
	Poster Board (Manual Feed)	Poster Board (Manual Feed)		
Paper Feed Method	Friction Feed	TOSIEL DOGIA (Manual Leeu)		
Maximum Roll Diameter	Max. 170 mm ⁻⁴			
Maximum Roll Weight	6.8kg			
Paper Width (Roll)	254 – 610 mm			
Paper Width (Cut Sheet)	203 – 610 mm			
Paper Thickness (Roll)	0.07 – 0.8 mm			
Paper Thickness (Manual)	Cut Sheet: 0.07 – 0.8 mm / Poster Board: 0.8 – 1.5 mm			
Maximum Printable Length	91 m ¹⁵			
Borderless Sizes		13"), 356mm (14"), 406mm (16"), 432mm		
Dall Dans an Barraria	(17"), 500mm (19"), 508mm (20"), 515mm (20.3"), 594mm (23"), 610mm (24")			
Roll Paper Remaining	The remaining amount is managed by the	le barcode printed on roll paper		
Connectivity	Cuparenand IER 100RACE TV/1000R	ASE T/IEEE000 11b/g/p/gg		
Interface	SuperSpeed USB, 100BASE-TX/1000B. USB Memory Stick	AOL-1/1EEE002.110/g/11/aC,		
Printer Language	ESC/P raster	ESC/P raster, HP-GL/2, HP RTL,		
		Adobe PostScript 3, Adobe PDF 1.7		
USB Direct Print	Yes			
Memory	4GB			
HDD (Optional)	SSD 960GB			
Operating System				
PC System Requirement	Windows 10, 8.1, 8, 7, Windows Vista, Windows XP (32bit/64bit)			
Mar O ala B	Windows Server 2019/2016/2012 R2/2012/2008/2003 R2/2003 SP2 or later			
Mac System Requirement	Mac OS X 10.6.8 or later, Mac OS 11 or	Taler		
Utility Software Bundled in CD	Windows - Printer driver - EnconNet Ser	un - EnsanNet Print - EnsanNet Config		
	Windows - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - EPSON manuals - Manual Launcher - LFP Print Plug-in for Office			
Web Delivery		Manager - Epson Device Admin - Epson		
- Vos Bonvory		Epson Print Automate - Order Controller		
	Mac - Printer driver - EpsonNet Config S			
	Installer - Epson Edge Dashboard - Epson			
	Epson Smart Panel			
Electrical Specifications				
Voltage	AC 100 - 240V, 50/60Hz			
Rated Current	AC 100V 3.4AAC 100-240V 3.4-1.6A			
Power Consumption	Operating: Approx. 75W, Ready: Approx			
	Sleep: Approx. 2W, Standby: Approx. 0.	3W		
Environmental Conditions	0 1 1000 1 0500 101			
Temperature	Operating: 10°C to 35°C / Storage: -20°C to 40°C			
Humidity	Operating: 20% to 80% (no condensation)			
Dimonoione & Wainbt	Storage: 5% to 85% (no condensation)			
Dimensions & Weight	1 365 v 400 v 075 mm			
Dimension (W x D x H) Weight	1,365 x 499 x 975 mm Approx. 115.2kg	Approx. 115.6kg		
	0	TAPPIOX. 110.0Ng		
 Might differ depends on applications/i ISO/IEC 24790, Single weight matte p Addressable. 	media. paper, CAD/line drawing, speed, high speed=Off, fines	st detail=On.		

- ⁴ Depending on the thickness of the paper. It is larger than the available outer diameter size. If roll paper is used, please confirm that it is
- within the outside diameter range.

 *5 Printable length is limited depending on restrictions of operating systems or applications.





Information correct at time of printing. Printed January 2023

Dimensions and Weight SC-P6530E Weight: Approx. 115.2kg

1.365mm

SC-P6530D Weight: Approx. 115.6kg

WHAT'S IN THE BOX PrinterInitial ink cartridge (110ml)

AC power cableSetup guideSoftware CD-ROM Maintenance box **OPTIONS**

Production Stacker (24") SSD Unit (C12C936671)

350ml 350ml

350ml

350ml 350ml

700ml

700ml

700ml 700ml

700ml

 Gley
 700ml
 C13143R800

 Matte Black
 700ml
 C13T48R800

 Maintenance Tank
 C13S210115

 Borderless Maintenance Box
 C13S210116

 Printer Cutter Blade
 C13S210117

 Cleaning Stick
 C13S090013

©2023 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks.

epson disclaims any arid air rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is

a service mark of Apple Inc. Android is a trademark of Google Inc.

CONSUMABLE Ink Cartridge

Photo Black

Grey Matte Black

Photo Black

Cyan Magenta

Yellow

Cyan

Magenta Yellow Grey Matte Black 499mm

499mm

C13T48Y100 C13T48Y200 C13T48Y300

C13T48Y400

C13T48YE00 C13T48Y800

C13T48R100 C13T48R200

C13T48R300 C13T48R400

C13T48RE00



EpsonSingapore EpsonSingapore EpsonSoutheastAsia in Epson Singapore Find out more at www.epson.com.sg/p-series

SPECIFICATIONS

MODEL NUMBER	SC-P8530D	SC-P8530DM	SC-P8530DL	Dimensions and Weight
SKU Number Printing Technology	C11CJ50402	C11CJ51402	C11CJ75402	SC-P8530D / P8530DM
Printing Method		echnology, Variable-Sized Dr	oplet Technology	Weight: Approx. 155kg
Print Head	PrecisionCore MicroTF	P Printhead		
Nozzle Configuration Black	9,600 Nozzles Pk:1,600, Mk:1,600			-
Colour	C:1,600, M:1,600, Y:1	,600, Gray:1,600		975mm
Maximum Resolution Minimum Ink Droplet Volume	2,400 x 1,200 dpi 3.5pl			
Printing Specifications	<u>5.5pi</u>			
Print Speed		sy Photo Paper 170gsm:		499mm
	152 sec (Speed), 281 Plain Paper: 35 sec (D	sec (Quality), 614 sec (Max (Praft), 46 sec (Speed), 258 se	Quality) ec (High Quality)	1,848mm
	Poster – B0 size Epso	n Premium Glossy Photo Pa	per 170gsm 1200dpi x 1200dpi:	SC-P8530DL
Mauria Dall Danas	Standard(sRGB)/Quali	ty: 281 sec		Weight: Approx. 165kg
Margin Roll Paper Cut Sheet	Right: Min. 3mm ⁻¹ / Le Top: Min. 3mm ⁻¹ / Bot	tom: Min. 1mm ^{*1}		
Scanning Specifications				11
Max. Scan Speed Max. Optical Resolution		<u>10 ips</u> 600 dpi		975mm
Scanning Specifications		<u>600 api</u>		
Max. Scan Speed	10 ips			
Max. Optical Resolution Copying Specifications	600 dpi			499mm
Scaling		25 – 755%	-	1,848mm
Max. Copy		99 copies		WILLIATIC IN THE DOX
Ink System Ink Type	Pigment Ink			WHAT'S IN THE BOX • Printer
Ink Brand Name	UltraChrome Pro 6 Ink			 Initial ink cartridge (110ml)
Colour		v, Grey, Photo Black, Matte E		AC power cableSetup guide
Ink Capacity Ink Case	350, 700 ml Ink Cartridge		1,600 ml Ink Supply Unit	 Software CD-ROM
	mik Gartrage		(Bulk Ink Solution)	 Maintenance box
Paper Handling	Dall (Davible Dall) Cut	Chast (Manual Food) Doctor	r Daard (Manual Faad)	OPTIONS
Paper Path Paper Feed Method	Friction Feed	Sheet (Manual Feed), Poster	Board (Manual Feed)	Roll Feed Spindle (44") (C12C936171)
Maximum Roll Diameter	Max. 170 mm ^{*2}			Production Stacker (44") (C12C937131) SSD Unit (C12C936671)
Maximum Roll Weight Paper Width (Roll)	12.5kg 254 – 1,118 mm			
Paper Width (Cut Sheet)	203 – 1,118 mm			CONSUMABLE Ink Cartridge
Paper Thickness (Roll)	0.07 – 0.8 mm			Photo Black 350ml C13T48Y100
Paper Thickness (Manual) Maximum Printable Length	Cut Sheet: 0.07 – 0.8 91 m ^{*3}	mm / Poster Board: 0.8 - 1.	5 mm	Cyan 350ml C13T48Y200
Borderless Sizes	254mm (10"), 300mm ((11.8"), 330mm (13"), 356mm	(14"), 406mm (16"), 432mm	Magenta 350ml C13T48Y300 Yellow 350ml C13T48Y400
	(17"), 500mm (19"), 508	8mm (20"), 515mm (20.3"), 59	94mm (23"), 610mm (24"),	Grey 350ml C13T48YE00
	700mm (27.5°), 728mn 1188mm (44°)	n (28.6"), 841mm (33"), 914m	m (36°), 1030mm (40.5°),	Matte Black 350ml C13T48Y800 Photo Black 700ml C13T48R100
Roll Paper Remaining		t is managed by the barcode	printed on roll paper	Cyan 700ml C13T48R200
Connectivity Interface				Magenta 700ml C13T48R300 Yellow 700ml C13T48R400
Printer Language	SuperSpeed USB ^{*1} , 100BASE-TX /1000BASE-T/IEEE802.11b/g/n/ac ESC/P raster, HP-GL/2*, HP RTL*, Adobe PostScript 3, Adobe PDF 1.7			Grey 700ml C13T48RE00
USB Direct Print	Yes			Matte Black 700ml C13T48R800 Maintenance Tank C13S210115
Memory HDD (Optional)	4GB SSD 960GB			Borderless Maintenance Box C13S210116
Operating System			 ,	Printer Cutter Blade C13S210117 Cleaning Stick C13S090013
PC System Requirement		', Windows Vista, Windows >		Clear III ig Stick C133090013
Mac System Requirement		0/2016/2012 R2/2012/2008/ oter, Mac OS 11 or later	2003 R2/2003 SP2 of later	00000 5 00 50 111 115 11 5
Utility Software				©2023 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written
Bundled in CD	Windows - Printer driv	⁄er - EpsonNet Setup - Epso - Manual Launcher - LFP Pri	nNet Print - EpsonNet Config	permission from Epson, is strictly prohibited.
	Driver - PS Folder			EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.
Web Delivery	Windows - Epson Med	dia Installer - EpsonNet Setu	pManager - Epson Device	All other product names and other company names used herein are for identification purposes only and
	Foson Edge Print (On	Jashboard - Epson Print Lay tion) - Epson Print Admin (Or	out - Epson Print Automate - otion) - Order Controller (Option)	are the trademarks or registered trademarks of their
	Mac - Printer driver - E	EpsonNet Config SE - EPSO	N manuals - Epson Media	respective owners. Epson disclaims any and all rights in those marks.
	Installer - Epson Edge	Dashboard - Epson Print La	ayout - PS DriveriOS/Android -	Projected images shown herein are simulations.
Electrical Specifications	Epson Smart Panel			The actual product design and contents may vary. Specifications are subject to change without notice an
Voltage	AC 100 - 240V, 50/60			may vary between countries. Please check with local Epson offices for more information.
Rated Current Power Consumption	AC 100V 3.4AAC 100 Operating: Approx. 70		Operating: Approx. 75W	Apple, iPad and iPhone are trademarks of Apple Inc.,
ower consumption	Ready: Approx. 32W		Ready: Approx. 32W	registered in the U.S. and other countries. App Store is a service mark of Apple Inc.
	Sleep: Approx. 2.0W	A.	Sleep: Approx. 2.0W	Android is a trademark of Google Inc.
Environmental Conditions	Standby: Approx. 0.3\	V	Standby: Approx. 0.3W	
Temperature		6°C / Storage: -20°C to 40°C		Dealer's Stamp
Humidity	Operating: 20% to 809	% (no condensation), Storag	e: 5% to 85% (no condensation)	
Dimensions & Weight Dimension (W x D x H)	1,848 x 499 x 975 mn	1		
Weight	Approx. 155kg		Approx. 165kg	
1 Might differ depends on applications/				Information correct at time of printing.
Depending on the thickness of the pa		le outer diameter size. If roll paper is	used, please confirm that it is	Printed January 2023
within the outside diameter range. 3 Printable length is limited depending of	on restrictions of operating sys	tems or applications.		
Find out more at www.epsor	ı.com.sg/p-series		EpsonSingapore O EpsonSinga	apore EpsonSoutheastAsia in Epson Singapore





